


**Notes**

- Where poor ground conditions are encountered, guidance on the depth and type of bedding shall be sought from the authority
- Commencing surface shall be :-
  - In existing roads* : Levels after removal of surfacing / roadbase
  - In proposed roads* : 300mm below proposed finished level
  - In arable and grass land* : Level after stripping topsoil
  - In waste ground* : original ground level
- Minimum cover to pipe 1.2m where vehicle will occur, 0.9m in all other locations. Where minimum cover cannot be achieved, concrete protection must be provided.

**BEDDING DETAIL FOR ALL PIPEWORK**

SCALE 1:20

 <p>1919</p> <p>Civil Engineers Structural Engineers Architects CDM Co-ordinators Geotechnical services Environmental services</p> <p>Stewart Building, Lerwick, Shetland, ZE1 0LL Tel : 01595 695512 - Fax : 01595 694401 www.arch-henderson.co.uk - email : lerwick@arch-henderson.co.uk</p> <p>Offices in : Aberdeen, Dundee, Glasgow, Lerwick, Lisboa (Portugal), Stromness and Thurso</p>	PROJECT :	DRAWN :	DATE :
	DRAINAGE DETAILS	AKT	DEC 2007
	TITLE :	SCALE : (A4) 1:20	CHECKED :
	PIPE BEDDING	DRAWING STATUS :	DRAWING No : AH-DR-07